



PRODUCT DATA SHEET

SKIMCOAT NỘI THẤT

Description	Skimcoat for patching and smoothing of interior wall.
Uses	Nippon SKIMCOAT NỘI THẤT is used as a putty for interior substrates such as: - Cement plasters - Concrete - Brickworks
Finish	Matt/ White
Features	- Easy application - Easy sanding - Create a very smooth surface
APPLICATION DATA	
Surface Preparation	Ensure the surface is clean and stable. Extremely dry and absorbent substrates should be moistened with water before applying Nippon SKIMCOAT NỘI THẤT.
Application Methods	Use trowel to apply Nippon SKIMCOAT NỘI THẤT on the surface with thickness of 1 mm depend on the surface. Wait for 16 hours or until the surface is partially settled then apply a second coat of similar thickness. Sanding the surface to give a smooth finish.
Paint Consumption	Theoretical: 30 - 40 m ² /bag (40Kg) depend on thickness applied
Mixing Instruction	Mix 01 bag Nippon SKIMCOAT NỘI THẤT with 14 - 16 liters of water (Use a mixer if available or adequate mixing equipment to mix for 5 - 10 minutes). Add powder to water to avoid lumpiness. Allow the mixture to stand for about 10 minutes then mix again until homogenous. Ready plaster should be used in 2 hours after mixing.
Cleaning	Wash all equipment immediately after use with clean water
Storage	Nippon SKIMCOAT NỘI THẤT is sensitive with moisture and water, keep the bags tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.
Packing	40 Kgs/Bag
Precaution	Do not use SKIMCOAT NỘI THẤT on unstable painted surfaces, water soluble plasters or smoothing floors.

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com

SKIMCOAT NỘI THẤT

	Do not apply SKIMCOAT NỘI THẤT when the temperature is below 10°C & moisture is over 85%.
NOTE	<i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product data sheet without further notice.</i>

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com