



Sơn Nippon  
Sơn Đẹp Cũng Đẹp

Ref. No. : PDS-0328-EN  
Version No. : 8  
Update Date : 10.10.20

## PRODUCT DATA SHEET

# ODOUR-LESS CHÙI RỬA VƯỢT TRỘI

<b>Description</b>	Nippon Paint ODOUR-LESS CHÙI RỬA VƯỢT TRỘI combines innovative paint technology with low environmental impact to give you our most advanced low odour paint. We hope you'll love it as much as we do – from its smooth even coverage to its rugged resistance to the assault of everyday life. ODOUR-LESS CHÙI RỬA VƯỢT TRỘI resists stains, wipes clean easily and is even scrubbable. So you'll get a beautiful rich finish for walls that looks good longer.
<b>Type</b>	Modified Acrylic Copolymer Emulsion
<b>Uses</b>	It is ideal for interior walls and ceilings such as: <ul style="list-style-type: none"> <li>- Cement plasters</li> <li>- Brickworks</li> <li>- Gypsum board</li> <li>- Concrete</li> <li>- Primed wood</li> <li>- Fiberboards ...</li> </ul>
<b>Finish</b>	Soft Matt Colour: Wide range of attractive colours as per colour card. Special colours on request.
<b>Features</b>	<p><b>Green properties:</b></p> <ul style="list-style-type: none"> <li>- Environmental friendly interior emulsion</li> <li>- Ultra-low VOCs (containing below 25g/L, meeting the VOC requirement)</li> <li>- Almost no odour during application and after drying</li> <li>- Non-toxic, does not contain lead, mercury, Cadmium and Chromium</li> <li>- APEO (Alkylphenol ethoxylates) free</li> <li>- Formaldehyde free</li> <li>- NMP (N-methyl pyrrolinone) free</li> </ul> <p><b>Clean Properties :</b></p> <ul style="list-style-type: none"> <li>- Stains on ODOUR-LESS CHÙI RỬA VƯỢT TRỘI can be removed easily</li> <li>- Excellent washability.</li> <li>- Long lasting colors</li> <li>- Good Alkaline &amp; Water resistance</li> <li>- Excellent coverage and hiding power</li> </ul>
<b>APPLICATION DATA</b>	
<b>Surface Preparation</b>	Surface must be clean, dry, and stable. <b>Suggested Treatment:</b> <u>Dirt/Powder:</u> Clean with damp cloth and remove loose powder. Mild detergent may be

## NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam  
Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

[www.nipponpaint.com](http://www.nipponpaint.com)

# ODOUR-LESS CHÙI RỬA VƯỢT TRỘI

	<p>used.</p> <p><u>Old Paint/Plaster/Skimcoat:</u> Unstable old film / substrate should be removed by chisel, scraper, power grinder whichever is appropriate. Uneven substrates must be re-plastered with an approved putty / skimcoat.</p> <p><u>Moisture:</u> High moisture will cause paint defect. Observe the following level prior to painting:</p> <ul style="list-style-type: none"> <li>- Masonry : below 6% by Sovereign 1150 Moisture meter below 16% by Protimeter Mini BLD 2000 Moisture meter below 60% by Lutron MS-7003 Moisture meter</li> </ul> <p>All water seepage must be checked and repaired.</p> <p><u>Algae/Fungus:</u> Remove by chisel or scraper and treat with NIPPON ANTI- FUNGUS SOLUTION. Rinse again with clean water and dry.</p> <p><u>Oil/Grease:</u> Clean off with mild detergent and a little solvent if necessary. Wash thoroughly to remove all trace.</p>
<b>Application Methods</b>	Brush, roller or airless spray
<b>Paint Consumption</b>	Theoretical: 12.0 m <sup>2</sup> / liter ( 30 microns DFT)
<b>Dilution</b>	Use clean water Roller & brush                                 - 20% maximum Airless Spray                                     - 10% maximum
<b>Spray Application</b>	<u>Airless Spray</u> Delivery Pressure (kg/cm <sup>2</sup> )             120 - 150 Tip size at 60° angle                     0.017" Dilution   10% maximum
<b>Recommended Painting System</b>	- 2- 3 coats SKIMCOAT NỘI THẤT - 1 coat ODOUR-LESS SEALER - 2 coats ODOUR-LESS CHÙI RỬA VƯỢT TRỘI
<b>Recommended Film Thickness</b>	30 - 40 microns DFT (Dry Film Thickness) per coat for standard application
<b>Drying Time</b>	Surface dry - 30 minutes at 30°C
<b>Overcoating Time</b>	2 hours. Minimum
<b>Cleaning</b>	Wash all equipment immediately after use with clean water
<b>Storage</b>	Keep containers tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.
<b>Packing</b>	1 Liters, 5 Liters and 18 Liters
<b>Precaution</b>	Avoid painting when the temperature is below 10°C and the humidity is over 85%. Avoid direct contact with sensitive skin. Use appropriate protective equipment. For an optimal easy-wash effect, the paint film should be fully dried in 5 days before use.

## NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

 www.nipponpaint.com

# ODOUR-LESS CHÙI RỬA VƯỢT TRỘI

	<p>The easy-wash effect will be better if the stains are removed earlier.</p> <p>The stains on wall can be removed by soft tower with diluted detergent or disk washing liquid.</p>
<b>NOTE</b>	<p><i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales &amp; Marketing Dept. We reserve the right to modify our product data sheet without further notice.</i></p>

## **NIPPON PAINT (VIETNAM) CO., LTD**

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

[www.nipponpaint.com](http://www.nipponpaint.com)