

Ref. No.: PDS-0328N-EN

Version No.: 0 Issued Date : 05.05.2021

PRODUCT DATA SHEET

ODOUR-LESS CHÙI RỬA VƯỢT TRỘI & KHÁNG KHUẨN

Description	Nippon Paint ODOUR-LESS CHÙI RỬA VƯỢT TRỘI & KHÁNG KHUẨN is speciall formulated product with easy clean performance and anti-bacterial properties. It resist stains and stains on painted surface can be cleaned easily.		
	ODOUR-LESS CHÙI RỬA VƯỢT TRỘI & KHÁNG KHUẨN is effective against many types of bacteria when existing on wall such as E. coli, Staphylococcus Aureus, Salmonella typhimurium, Shigella flexneri, Pseudomonas aeruginosa, Klebsiella pneumoniae, Listeria monocytogenes which cause variety of infection in human.		
	So you'll get a beautiful r	rich finish for walls that looks g	ood & lasts longer.
Туре	Modified Acrylic Copolymer Emulsion		
Uses	It is ideal for interior walls and ceilings such as:		
	- Cement plasters - Concrete	BrickworksPrimed wood	Gypsum boardFiberboards
Finish	Soft Matt Colour: Wide range of attractive colours as per colour card. Special colours on request.		
Features	 Stains on ODOUR-LESS CHÙI RỬA VƯỢT TRỘI & KHÁNG KHUẨN can be cleaned easily Excellent washability. Anti-bacterial (effective against common bacteria when existing on wall such as E. coli, Staphylococcus Aureus, Salmonella typhimurium, Shigella flexneri, Pseudomonas aeruginosa, Klebsiella pneumoniae, Listeria monocytogenes) Long lasting colors Good Alkaline & Water resistance Excellent coverage and hiding power Ultra-low VOCs (containing below 25g/L, meeting the VOC requirement) Almost no odour during application and after drying NOTE: Nippon Paint ODOUR-LESS CHÙI RỬA VƯỢT TRỘI & KHÁNG KHUẨN serves to reduce the transmission of bacteria through inactivation process on painted surface. It does not warranty users' immunity to bacteria. 		
APPLICATION DATA			
Surface Preparation	Surface must be clean, d	ry, and stable.	

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349



ODOUR-LESS KHÁNG KHUẨN & CHÙI RỬA VƯỢT TRỘI

	I			
	Suggested Treatment:			
	<u>Dirt/Powder:</u> Clean with damp cloth and remove loose powder. Mild detergent may be			
	used.			
	Old Paint/Plaster/Skimcoat: Unstable old film / substrate should be removed by chisel,			
	scraper, power grinder whichever is appropriate. Uneven substrates must be re-plastered			
	with an approved putty / skimcoat.			
	Moisture: High moisture will cause paint defect. Observe the following level prior to			
	painting:			
	- Masonry : below 16% by Protimeter Mini BLD 2000 Moisture meter			
	below 60% by Lutron MS-7003 Moisture meter			
	All water seepage must be checked and repaired.			
	, -			
	Algae/Fungus: Remove by chisel or scraper and treat with NIPPON ANTI- FUNGUS			
	SOLUTION. Rinse again with clean water and dry.			
	Oil/Grease: Clean off with mild detergent and a little solvent if necessary. Wash			
	thoroughly to remove all trace.			
Application	Brush, roller or airless spray			
Methods				
Paint Consumption	Theoretical: 12.0 m²/ liter (30 microns DFT)			
-	· · · · · · · · · · · · · · · · · · ·			
Dilution	Use clean water			
	Roller & brush	- 20% maximum		
	Airless Spray	- 10% maximum		
Spray Application		Airless Spray		
' ' ' ' '	Delivery Pressure (kg/cm²)	120 - 150		
	Tip size at 60° angle	0.017"		
	Dilution	10% maximum		
Recommended	- 2- 3 coats SKIMCOAT NỘI THẤT			
Painting System	- 1 coat ODOUR-LESS SEALE			
	- 2 coats ODOUR-LESS CHÙI	RỬA VƯỢT TRỘI & KHÁNG KHUẪN		
Recommended Film	30 - 40 microns DET /Dry Film	Thickness) per coat for standard application		
Thickness	30 - 40 microns DFT (Dry Film Thickness) per coat for standard application			
Drying Time	Surface dry - 30 minutes at 30°	C		
Overcoating Time	2 hours. Minimum			
Cleaning	Wash all equipment immediately after use with clean water			
Storage	Keep containers tightly closed. Store in cool, dry and well-ventilated place at			
	temperature between 5 to 40°C.			
Pooking	1 Liter E Litera and 45 Litera			
Packing	1 Liter, 5 Liters and 15 Liters			
Precaution	Avoid painting when the temperature is below 10°C and the humidity is over 85%. Avoid			
	direct contact with sensitive ski	n. Use appropriate protective equipment.		
	direct contact with sensitive ski	n. Use appropriate protective equipment.		

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349



ODOUR-LESS KHÁNG KHUẨN & CHÙI RỬA VƯỢT TRỘI

	For an optimal easy-wash effect, the paint film should be fully dried in 5 days before use. The easy-wash effect will be better if the stains are removed earlier. The stains on wall can be removed by soft tower with diluted detergent or disk washing liquid.
NOTE	The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product data sheet without further notice.

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

