

## PRODUCT DATA SHEET

**NIPPON INTERIOR PUTTY**

<b>Description</b>	Putty for patching and smoothening of interior wall.
<b>Uses</b>	NIPPON INTERIOR PUTTY is used for interior substrates such as: - Cement plasters                      - Concrete                      - Brickworks
<b>Finish</b>	Matt/ White
<b>Features</b>	<ul style="list-style-type: none"> <li>- Easy application</li> <li>- Easy sanding</li> <li>- Create a very smooth surface</li> </ul>
<b>APPLICATION DATA</b>	
<b>Surface Preparation</b>	<p>Ensure the surface is clean and stable.</p> <ul style="list-style-type: none"> <li>- Masonry: below 16% by Protimeter Mini BLD 2000 Moisture meter                below 60% by Lutron MS-7003 Moisture meter</li> </ul> <p>Extremely dry and absorbent substrates should be moistened with water before applying NIPPON INTERIOR PUTTY</p>
<b>Application Methods</b>	<p>Use trowel to apply NIPPON INTERIOR PUTTY on the surface with thickness of 1 mm depend on the surface.</p> <p>Wait for 16 hours or until the surface is partially settled then apply a second coat of similar thickness.</p> <p>Sanding the surface to give a smooth finish.</p>
<b>Paint Consumption</b>	Theoretical: 30 - 40 m <sup>2</sup> /bag (40Kg) depend on thickness applied
<b>Mixing Instruction</b>	<p>Mix 01 bag NIPPON INTERIOR PUTTY with 14 - 16 liters of water (Use a mixer if available or adequate mixing equipment to mix for 5 - 10 minutes).</p> <p>Add powder to water to avoid lumpiness.</p> <p>Allow the mixture to stand for about 10 minutes then mix again until homogenous.</p> <p>Ready plaster should be used in 2 hours after mixing.</p>
<b>Cleaning</b>	Wash all equipment immediately after use with clean water
<b>Storage</b>	NIPPON INTERIOR PUTTY is sensitive with moisture and water, keep the bags tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.
<b>Packing</b>	40 Kgs/Bag

**NIPPON PAINT (VIETNAM) CO., LTD**

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam  
 Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349



## NIPPON INTERIOR PUTTY

<b>Precaution</b>	<p>Coverage depends on film thickness, roughness or porosity of the surface, loss during painting, etc.</p> <p>The actual drying time and time before recoating may be shorter or longer, depending on film thickness, temperature, ambient humidity, ventilation, etc.</p> <p>Do not use NIPPON INTERIOR PUTTY on unstable painted surfaces, water soluble plasters or smoothing floors.</p> <p>Do not apply NIPPON INTERIOR PUTTY when the temperature is below 10°C &amp; moisture is over 85%.</p>
<b>NOTE</b>	<p><i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales &amp; Marketing Dept. We reserve the right to modify our product data sheet without further notice.</i></p>

### **NIPPON PAINT (VIETNAM) CO., LTD**

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

[www.nipponpaint.com](http://www.nipponpaint.com)