

PRODUCT DATA SHEET

SPOT-LESS PLUS

Description	<p>Nippon Paint SPOT-LESS PLUS is an outstanding interior paint with Anti-Stain Technology that makes it an excellent hydrophilic stain repellent with very high resistance to household stains such as tea, wine, coffee, inks, hand marks, lipstick, juice, etc.</p> <p>Besides, SPOT-LESS PLUS is formulated with Silver Ion Technology that is proven 99.9% effective against COVID-19 (SARS-CoV-2), other harmful viruses and bacteria when existing on walls.</p> <p>Long-lasting, beauty and wide range of attractive colors.</p> <p>Note: Excellent hydrophilic stain repellence means that SPOT-LESS PLUS not only has a high ability to resist the penetration of hydrophilic liquid stains but also has beading effects on all these stains. The hydrophilic liquid stain will form into beads on the paint film and roll down the wall, therefore, making the paint surfaces easier to clean.</p>
Type	Acrylic Copolymer Emulsion
Uses	<p>It is ideal for interior walls and ceilings such as:</p> <ul style="list-style-type: none"> - Cement plasters - Brickworks - Gypsum board - Concrete - Primed wood - Fiberboards ...
Finish	<p>Low Sheen</p> <p>Colours: Wide range of attractive colours as per colour card. Special colours on request.</p>
Features	<ul style="list-style-type: none"> - Excellent stain repellent by Anti-Stain Technology to resist the penetration of hydrophilic liquid stains and has beading effects on all these stains - Excellent washability - Anti-viral (effective against harmful viruses such as SARS-CoV-2) by Silver Ion Technology 99.9% effective against COVID-19 (SARS-CoV-2) - Outstanding product with advance colour technology bring the creative experience with many colour choices, beauty and long-lasting colour. - Anti-bacterial (effective against common bacteria such as E. Coli, Staphylococcus Aureus, Salmonella typhimurium, Shigella flexneri, Pseudomonas aeruginosa, Klebsiella pneumoniae, Listeria monocytogenes) - Excellent water resistance and anti-fungus properties - Excellent coverage and hiding power - Extra low odour during application and after drying - Non-toxic, APEO free, does not contain Lead, Mercury and heavy metals

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam
 Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com

SPOT-LESS PLUS

	<ul style="list-style-type: none"> - Low VOCs (containing < 10g/L VOC, meeting the VOC requirement) - Green Label Certificate <p>NOTE: SPOT-LESS PLUS serves to reduce the transmission of viruses and bacteria through the inactivation process on the painted surface. It does not warranty users' immunity to viruses and bacteria.</p>						
APPLICATION DATA							
Surface Preparation	<p>The surface must be clean, dry and stable.</p> <p><u>Suggested treatment:</u></p> <p><u>Dirt/Powder:</u> Clean with a damp cloth and remove the loose powder. Mild detergent may be used.</p> <p><u>Old Paint/Plaster/Putty:</u> Unstable old film/substrate should be removed by chisel, scraper, or power grinder whichever is appropriate. Uneven substrates must be re-plastered with an approved putty/skimcoat.</p> <p><u>Moisture:</u> High moisture will cause paint defects. Observe the following level prior to painting:</p> <ul style="list-style-type: none"> - Masonry: below 16% by Protimeter Mini BLD 2000 Moisture meter below 60% by Lutron MS-7003 Moisture meter <p>All water seepage must be checked and repaired.</p> <p><u>Algae/Fungus:</u> Remove by chisel or scraper and treat with NIPPON ANTI- FUNGUS SOLUTION. Rinse again with clean water and dry.</p> <p><u>Oil/Grease:</u> Clean off with mild detergent and a little solvent if necessary. Wash thoroughly to remove all traces.</p>						
Application Methods	Brush, roller or airless spray						
Paint Consumption	Theoretical: 9.8 - 13.0 m ² / liter (30 - 40 microns DFT)						
Dilution	<p>Use clean water</p> <table style="width: 100%; border: none;"> <tr> <td style="width: 60%;">Roller & brush</td> <td style="width: 40%;">- 10% maximum Preferable not dilute for best performance</td> </tr> <tr> <td>Airless Spray</td> <td>- No dilution</td> </tr> </table>	Roller & brush	- 10% maximum Preferable not dilute for best performance	Airless Spray	- No dilution		
Roller & brush	- 10% maximum Preferable not dilute for best performance						
Airless Spray	- No dilution						
Spray Application	<p style="text-align: right;"><u>Airless Spray</u></p> <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Delivery Pressure (kg/cm²)</td> <td style="width: 50%;">120 - 150</td> </tr> <tr> <td>Tip size at 60° angle</td> <td>0.017"</td> </tr> <tr> <td>Dilution</td> <td>No</td> </tr> </table>	Delivery Pressure (kg/cm ²)	120 - 150	Tip size at 60° angle	0.017"	Dilution	No
Delivery Pressure (kg/cm ²)	120 - 150						
Tip size at 60° angle	0.017"						
Dilution	No						
Recommended Painting System	<ul style="list-style-type: none"> - 1 - 2 coats NIPPON INTERIOR PUTTY or SKIMCOAT NỘI THẤT - 1 coat ODOUR-LESS SEALER - 2 coats SPOT-LESS PLUS 						
Recommended Film Thickness	30 - 40 microns DFT (Dry Film Thickness) per coat for standard application						

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam
Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com

SPOT-LESS PLUS

Drying Time	Surface dry: 30 minutes at 30°C
Overcoating Time	2 hours. Minimum based on normal conditions
Cleaning	Wash all equipment immediately after use with clean water
Storage	Keep containers tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.
Packing	1 Liter, 5 Liters & 15 Liters
Precaution	<p>Coverage depends on film thickness, roughness or porosity of the surface, loss during painting, etc.</p> <p>The actual drying time and time before recoating may be shorter or longer, depending on film thickness, temperature, ambient humidity, ventilation, etc.</p> <p>Avoid painting when the temperature is below 10°C and the humidity is over 85%. Avoid direct contact with sensitive skin. Use appropriate protective equipment.</p> <p>For an optimal easy-wash effect, the paint film should be fully dried in 5 days before use. The easy-wash effect will be better if the stains are removed earlier.</p> <p>The stains on the wall can be removed by a soft towel with diluted detergent or disk washing liquid</p>
NOTE	<p><i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for the specific application, please contact Sales & Marketing Dept of Nippon Paint (Vietnam) Co. Ltd. We reserve the right to modify our product data sheet without further notice.</i></p>

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Binh Tan Ward, Bien Hoa City, Dong Nai Province, Vietnam
Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com