Version No: 1
Issued Date: 03.11.25

PRODUCT DATA SHEET

EASY WASH

Description	EASY WASH is a premium interior paint with easy to clean properties and a smooth finish that brings a feeling of comfort and relaxation. With EZWash technology, stains can be easily to clean, making this product the best choice for modern and sophisticated living spaces.
Type	Modified Acrylic Emulsion
Uses	It is ideal for interior such as: - Cement plasters - Brickworks - Gypsum board - Concrete - Primed wood - Fiberboards …
Finish	Matt Colour: Wide range of attractive colours as per colour card. Special colours on request.
Features	- Excellent easy to clean with EZWash Technology easily removes stains such as coffee, tea, ... - The paint film is smooth & beautiful with Colour Guard Technology - Excellent coverage and hiding power. - Extra low odour during application and after drying. - Anti-fungus properties - Excellent adhesion on stable substrates - Non-toxic, does not contain Lead, Mercury, Chrome, Mercury and heavy metals - Low VOCs (containing < 25g/L VOC, meeting the VOC requirement) - Green Label Certificate - Comply with National technical regulation QCVN 08:2020/BCT on the limits of Lead content in paints.
APPLICATION DATA	
Surface Preparation	Surface must be clean, dry, and stable. **<u>Suggested Treatment:</u>** <u>Dirt/Powder:</u> Clean with damp cloth and remove loose powder. Mild detergent may be used. <u>Old Paint/Plaster/Skimcoat:</u> Unstable old film / substrate should be removed by chisel, scraper, power grinder whichever is appropriate. Uneven substrates must be re-plastered with an approved putty / skimcoat. <u>Moisture:</u> High moisture will cause paint defect. Observe the following level prior to painting: - Masonry: below 16% by Protimeter Mini BLD 2000 Moisture meter below 60% by Lutron MS-7003 Moisture meter

NIPPON PAINT (VIETNAM) CO., LTD
No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Hung Ward, Dong Nai City, Vietnam
Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349
www.nipponpaint.com

A MEMBER OF THE NIPSEA GROUP

	All water seepage must be checked and repaired. Algae/Fungus: Remove by chisel or scraper and treat with ANTI - FUNGUS SOLUTION. Rinse again with clean water and dry. Oil/Grease: Clean off with mild detergent and a little solvent if necessary. Wash thoroughly to remove all trace.
Application Methods	Brush, roller or airless spray
Paint Consumption	Theoretical: 10.0 - 13.0 m^2/ liter (30 - 40 microns DFT)
Dilution	Not more than 15% of clean water if required Roller & brush - 15% maximum Airless Spray - 10% maximum
Spray Application	Airless Spray Delivery Pressure (kg/cm^2) 120 - 150 Tip size at 60° angle 0.017'' Dilution 10% maximum
Recommended Painting System	- 1 - 2 coats NIPPON INTERIOR PUTTY - 1 coat EASY WASH SEALER - 2 coats EASY WASH
Recommended Film Thickness per coat	30 - 40 microns DFT (Dry Film Thickness) per coat for standard application
Drying Time	Surface dry: 30 minutes at 30°C
Overcoating Time	2 hours. Minimum based on normal conditions.
Cleaning	Wash all equipment immediately after use with clean water
Storage	Keep containers tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.
Packing	5 Liters & 15 Liters Containers
Precaution	Coverage depends on film thickness, roughness or porosity of the surface, loss during painting, etc. The actual drying time and time before recoating may be shorter or longer, depending on film thickness, temperature, ambient humidity, ventilation, etc. Avoid painting when the temperature is below 10°C and the humidity is over 85%. Avoid direct contact with sensitive skin. Use appropriate protective equipment.
NOTE	*The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product data sheet without further notice.*

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Hung Ward, Dong Nai City, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com

A MEMBER OF THE NIPSEA GROUP