
PRODUCT DATA SHEET

NIPPON INTERIOR PUTTY

Description	Putty for patching and smoothening of interior wall.
Uses	NIPPON INTERIOR PUTTY is used for interior substrates such as: - Cement plasters - Concrete - Brickworks
Finish	Matt/ White
Features	- Easy application - Easy sanding - Create a very smooth surface
APPLICATION DATA	
Surface Preparation	Ensure the surface is clean and stable. - Masonry: below 16% by Protimeter Mini BLD 2000 Moisture meter below 60% by Lutron MS-7003 Moisture meter Extremely dry and absorbent substrates should be moistened with water before applying NIPPON INTERIOR PUTTY
Application Methods	Use trowel to apply NIPPON INTERIOR PUTTY on the surface with thickness of 1 mm depend on the surface. Wait for 16 hours or until the surface is partially settled then apply a second coat of similar thickness. Sanding the surface to give a smooth finish.
Paint Consumption	Theoretical: 30 - 40 m ² /bag (40Kg) depend on thickness applied
Mixing Instruction	Mix 01 bag NIPPON INTERIOR PUTTY with 14 - 16 liters of water (Use a mixer if available or adequate mixing equipment to mix for 5 - 10 minutes). Add powder to water to avoid lumpiness. Allow the mixture to stand for about 10 minutes then mix again until homogenous. Ready plaster should be used in 2 hours after mixing.
Cleaning	Wash all equipment immediately after use with clean water
Storage	NIPPON INTERIOR PUTTY is sensitive with moisture and water, keep the bags tightly closed. Store in cool, dry and well-ventilated place at temperature between 5 to 40°C.
Packing	40 Kgs/Bag

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Hung Ward, Dong Nai City, Vietnam
Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com

NIPPON INTERIOR PUTTY

Precaution	Coverage depends on film thickness, roughness or porosity of the surface, loss during painting, etc. The actual drying time and time before recoating may be shorter or longer, depending on film thickness, temperature, ambient humidity, ventilation, etc. Do not use NIPPON INTERIOR PUTTY on unstable painted surfaces, water soluble plasters or smoothening floors. Do not apply NIPPON INTERIOR PUTTY when the temperature is below 10°C & moisture is over 85%.
NOTE	<i>The information given applies to the product and its performance under specific test conditions. Due to the varied circumstances beyond our control under which the product may be applied, for specific application, please contact Nippon Paint Sales & Marketing Dept. We reserve the right to modify our product data sheet without further notice.</i>

NIPPON PAINT (VIETNAM) CO., LTD

No. 14, 3A Road, Bien Hoa Industrial Zone II, Long Hung Ward, Dong Nai City, Vietnam

Tel: (84).251.3836579 – 3836586 (8 lines), Fax: (84).251.3836346 – 3836349

www.nipponpaint.com